

## CLAIMS

1           1.       (currently amended) A method for processing audio signals generated by an array of two  
2 or more microphones, comprising the steps of:

3           (a)       filtering the audio signal from each microphone to generate a processed audio signal for  
4 each microphone; and

5           (b)       combining the processed audio signals in a nonlinear manner that suppresses effects of  
6 high values to form an acoustic beam that focuses the array on one or more desired regions in space by  
7 performing nonlinear signal estimation processing on the processed audio signals from the microphones  
8 to generate an output signal for the array, wherein the nonlinear signal estimation processing  
9 discriminates against noise originating at an unknown location outside of the one or more desired  
10 regions.

1           2.       (original) The invention of claim 1, wherein step (a) comprises the step of delaying and  
2 scaling the audio signal from each microphone.

1           3.       (original) The invention of claim 1, wherein step (a) comprises the step of applying a  
2 digital filter corresponding to the inverse of each transfer function from a desired focal point to each  
3 microphone to compensate for reverberation in a volume containing the array.

1           4.       (original) The invention of claim 1, wherein the output signal is processed in a feedback  
2 loop to generate control signals that adjust the nonlinear signal estimation processing of step (b).

1           5.       (original) The invention of claim 4, wherein the control signals adjust weights applied to  
2 the processed audio signals during the nonlinear signal estimation processing of step (b).

1           6.       (original) The invention of claim 5, wherein a weight for each processed audio signal is  
2 based on a ratio of power in a speech band to power outside the speech band for the processed audio  
3 signal.

1           7.       (original) The invention of claim 4, wherein the output signal is processed in another  
2 feedback loop to generate other control signals that adjust the filtering of step (a) to attempt to match  
3 each of the processed audio signals.

1           8.       (original) The invention of claim 1, wherein the output signal is processed in a feedback  
2 loop to generate control signals that adjust the filtering of step (a).

1           9.       (original) The invention of claim 1, wherein the filtering of step (a) is dynamically  
2 adjusted to attempt to match each of the processed audio signals.

1           10.       (original) The invention of claim 9, wherein the filtering of step (a) is dynamically  
2 adjusted to attempt to match each of the processed audio signals in amplitude and phase to each other and  
3 to the output signal.

1           11.       (original) The invention of claim 1, wherein the nonlinear signal estimation processing  
2 picks a representative, central value from the processed audio signals, by altering at least one extreme  
3 value from at least one of the processed audio signals.

1           12.     (original) The invention of claim 11, wherein the nonlinear signal estimation processing  
2 comprises the step of selecting the representative, central value as a median of the processed audio  
3 signals.

1           13.     (original) The invention of claim 11, wherein the nonlinear signal estimation processing  
2 comprises the steps of:  
3           (1)     adjusting the magnitude of one or more of at least one of the highest and lowest values of  
4 the processed audio signals to generate a set of adjusted audio signals; and  
5           (2)     selecting the representative, central value as a median or average of the adjusted audio  
6 signals.

1           14.     (original) The invention of claim 13, wherein:  
2           step (1) comprises the steps of:  
3                 (i)     adjusting the value of the  $n$  highest values down to match the  $(n+1)^{\text{th}}$  highest data  
4 value, where  $n$  is a non-negative integer; and  
5                 (ii)    adjusting the value of the  $m$  lowest values up to match the  $(m+1)^{\text{th}}$  lowest data  
6 value, where  $m$  is a non-negative integer; and  
7           step (2) comprises the step of selecting the representative, central value as an average of the  
8 processed audio signals.

1           15.     (original) The invention of claim 14, wherein the average is a weighted average.

1           16.     (original) The invention of claim 11, wherein the nonlinear signal estimation processing  
2 comprises the steps of:  
3           (1)     dropping one or more of the highest and lowest values of the processed audio signals to  
4 generate a set of adjusted audio signals; and  
5           (2)     selecting the representative, central value as an average of the adjusted audio signals.

1           17.     (original) The invention of claim 16, wherein the average is a weighted average.

1           18.     (original) The invention of claim 1, wherein the nonlinear signal estimation processing  
2 treats each set of input values for the processed audio signals independently.

1           19.     (original) The invention of claim 1, wherein the nonlinear signal estimation processing  
2 is based on multiple values from each processed audio signal over a period of time.

1           20.     (original) The invention of claim 19, wherein the nonlinear signal estimation processing  
2 comprises the step of applying temporal filtering to the input values of each processed audio signal.

1           21.     (original) The invention of claim 20, wherein the nonlinear signal estimation processing  
2 further comprises the steps of generating a distance measure between pairs of audio signals and  
3 generating the output signal from the one or more audio signals having the smallest distance measures  
4 with other audio signals.

1           22.     (currently amended) A machine-readable medium, having encoded thereon program  
2 code, wherein, when the program code is executed by a machine, the machine implements a method for  
3 processing audio signals generated by an array of two or more microphones, comprising the steps of:  
4           (a)     filtering the audio signal from each microphone to generate a processed audio signal for  
5 each microphone; and

6 (b) combining the processed audio signals in a nonlinear manner that suppresses effects of  
7 high values to form an acoustic beam that focuses the array on one or more desired regions in space by  
8 performing nonlinear signal estimation processing on the processed audio signals from the microphones  
9 to generate an output signal for the array, wherein the nonlinear signal estimation processing  
10 discriminates against noise originating at an unknown location outside of the one or more desired  
11 regions.

1 23. (currently amended) A method for processing audio signals generated by an array of two  
2 or more microphones, comprising the steps of:

3 (a) filtering the audio signal from each microphone to generate a processed audio signal for  
4 each microphone; and

5 (b) combining the processed audio signals in a nonlinear manner to form an acoustic beam  
6 that focuses the array on one or more desired regions in space[; and (b)] by performing nonlinear signal  
7 estimation processing on the processed audio signals from the microphones to generate an output signal  
8 for the array, wherein the nonlinear signal estimation processing discriminates against noise originating  
9 at an unknown location outside of the one or more desired regions, wherein step (a) comprises the step of  
10 applying a digital filter corresponding to the inverse of each transfer function from a desired focal point  
11 to each microphone to compensate for reverberation in a volume containing the array.

1 24. (currently amended) A method for processing audio signals generated by an array of two  
2 or more microphones, comprising the steps of:

3 (a) filtering the audio signal from each microphone to generate a processed audio signal for  
4 each microphone; and

5 (b) combining the processed audio signals in a nonlinear manner to form an acoustic beam  
6 that focuses the array on one or more desired regions in space[; and (b)] by performing nonlinear signal  
7 estimation processing on the processed audio signals from the microphones to generate an output signal  
8 for the array, wherein the nonlinear signal estimation processing discriminates against noise originating  
9 at an unknown location outside of the one or more desired regions, wherein the output signal is processed  
10 in a feedback loop to generate control signals that adjust the nonlinear signal estimation processing of  
11 step (b).

1 25. (previously presented) The invention of claim 24, wherein the control signals adjust  
2 weights applied to the processed audio signals during the nonlinear signal estimation processing of step  
3 (b).

1 26. (previously presented) The invention of claim 25, wherein a weight for each processed  
2 audio signal is based on a ratio of power in a speech band to power outside the speech band for the  
3 processed audio signal.

1 27. (previously presented) The invention of claim 24, wherein the output signal is processed  
2 in another feedback loop to generate other control signals that adjust the filtering of step (a) to attempt to  
3 match each of the processed audio signals.

1 28. (currently amended) A method for processing audio signals generated by an array of two  
2 or more microphones, comprising the steps of:

3 (a) filtering the audio signal from each microphone to generate a processed audio signal for  
4 each microphone; and

5 (b) combining the processed audio signals in a nonlinear manner to form an acoustic beam  
6 that focuses the array on one or more desired regions in space[; and (b)] by performing nonlinear signal  
7 estimation processing on the processed audio signals from the microphones to generate an output signal

8 for the array, wherein the nonlinear signal estimation processing discriminates against noise originating  
9 at an unknown location outside of the one or more desired regions, wherein the output signal is processed  
10 in a feedback loop to generate control signals that adjust the filtering of step (a).

1 29. (canceled)

1 30. (currently amended) A method for processing audio signals generated by an array of two  
2 or more microphones, comprising the steps of:

3 (a) filtering the audio signal from each microphone to generate a processed audio signal for  
4 each microphone; and

5 (b) combining the processed audio signals in a nonlinear manner to form an acoustic beam  
6 that focuses the array on one or more desired regions in space[; and (b)] by performing nonlinear signal  
7 estimation processing on the processed audio signals from the microphones to generate an output signal  
8 for the array, wherein the nonlinear signal estimation processing discriminates against noise originating  
9 at an unknown location outside of the one or more desired regions, wherein the nonlinear signal  
10 estimation processing picks a representative, central value from the processed audio signals, by altering  
11 at least one extreme value from at least one of the processed audio signals, wherein the nonlinear signal  
12 estimation processing comprises the steps of:

13 (1) adjusting the magnitude of one or more of at least one of the highest and lowest values of  
14 the processed audio signals to generate a set of adjusted audio signals; and

15 (2) selecting the representative, central value as a median or average of the adjusted audio  
16 signals.

1 31. (previously presented) The invention of claim 30, wherein the nonlinear signal  
2 estimation processing comprises the step of selecting the representative, central value as a median of the  
3 processed audio signals.

1 32. (canceled)

1 33. (currently amended) The invention of claim [[13]] 30, wherein:  
2 step (1) comprises the steps of:

3 (i) adjusting the value of the  $n$  highest values down to match the  $(n+1)^{\text{th}}$  highest data  
4 value, where  $n$  is a non-negative integer; and

5 (ii) adjusting the value of the  $m$  lowest values up to match the  $(m+1)^{\text{th}}$  lowest data  
6 value, where  $m$  is a non-negative integer; and

7 step (2) comprises the step of selecting the representative, central value as an average of the  
8 processed audio signals.

1 34. (previously presented) The invention of claim 33, wherein the average is a weighted  
2 average.

1 35-36. (canceled)

1 37. (currently amended) A method for processing audio signals generated by an array of two  
2 or more microphones, comprising the steps of:

3 (a) filtering the audio signal from each microphone to generate a processed audio signal for  
4 each microphone; and

5 (b) combining the processed audio signals in a nonlinear manner to form an acoustic beam  
6 that focuses the array on one or more desired regions in space[; and (b)] by performing nonlinear signal  
7 estimation processing on the processed audio signals from the microphones to generate an output signal

8 for the array, wherein the nonlinear signal estimation processing discriminates against noise originating  
9 at an unknown location outside of the one or more desired regions, wherein:

10 the nonlinear signal estimation processing is based on multiple values from each  
11 processed audio signal over a period of time; and

12 the nonlinear signal estimation processing comprises the steps of:  
13 applying temporal filtering to the input values of each processed audio signal;  
14 generating a distance measure between pairs of audio signals; and  
15 generating the output signal from the one or more audio signals having the  
16 smallest distance measures with other audio signals.

1 38. (canceled)

1 39. (new) The invention of claim 28, wherein the filtering of step (a) is dynamically  
2 adjusted to attempt to match each of the processed audio signals.

1 40. (new) The invention of claim 39, wherein the filtering of step (a) is dynamically  
2 adjusted to attempt to match each of the processed audio signals in amplitude and phase to each other and  
3 to the output signal.

1 41. (new) A method for processing audio signals generated by an array of two or more  
2 microphones, comprising the steps of:

3 (a) filtering the audio signal from each microphone to generate a processed audio signal for  
4 each microphone; and

5 (b) combining the processed audio signals in a nonlinear manner to form an acoustic beam  
6 that focuses the array on one or more desired regions in space by performing nonlinear signal estimation  
7 processing on the processed audio signals from the microphones to generate an output signal for the  
8 array, wherein the nonlinear signal estimation processing discriminates against noise originating at an  
9 unknown location outside of the one or more desired regions, wherein the nonlinear signal estimation  
10 processing picks a representative, central value from the processed audio signals, by altering at least one  
11 extreme value from at least one of the processed audio signals, wherein the nonlinear signal estimation  
12 processing comprises the steps of:

13 (1) dropping one or more of the highest and lowest values of the processed audio signals to  
14 generate a set of adjusted audio signals; and

15 (2) selecting the representative, central value as an average of the adjusted audio signals.

1 42. (new) The invention of claim 41, wherein the average is a weighted average.